

ANTIGRAVITY BATTERIES

PRODUCT SAFETY INFORMATION GUIDE

IMPORTANT! READ FIRST

⚠ DANGER

READ AND UNDERSTAND ALL SAFETY INFORMATION BEFORE USING THIS PRODUCT. Failure to follow these safety instructions may result in **ELECTRICAL SHOCK, EXPLOSION, FIRE, DEATH, or PROPERTY DAMAGE.**

Electrical Shock. Product is an electrical device that can shock and cause serious injury. Do not cut power cords or short-circuit. Do not submerge or get wet.

Explosion. Unmonitored, incompatible, or damaged batteries can explode if used with product. Do not leave product unattended while in use. Do not attempt to jump-start a damaged or frozen battery. Use product only with batteries of recommended voltage. Operate product in well ventilated areas.

Fire. Product is an electrical device that emits heat and is capable of causing burns. Do not cover product. Do not smoke or use any source of electrical spark or fire when operating product. Keep product away from combustible materials.

⚠ DANGER

Eye Injury. Wear eye protection when operating product. Batteries can explode and cause flying debris. Battery acid can cause eye and skin irritation. In the case of contamination of eyes or skin, flush affected area with running clean water and contact poison control immediately.

Explosive Gases. Working in the vicinity of gases is dangerous. Batteries may generate explosive gases during normal battery operation. To reduce risk of battery explosion, follow all safety information instructions and those published by the battery manufacturer and manufacturer of any equipment intended to be used in the vicinity of battery. Review cautionary markings on these products and on engine.

Important Safety Warnings

- PERSONAL PRECAUTION.** Only use product as intended.
- Someone should be within range of your voice or close enough to come to your aid in case of emergency.
 - Have a supply of clean water and soap nearby in the case of battery acid contamination.
 - Wear complete eye protection and protective clothing while working near a battery.
 - Always wash hands after handling batteries and related materials.
 - Do not handle or wear any metal objects when working with batteries, including tools, watches or jewelry. If metal is dropped onto battery, it may spark or create a short circuit resulting in electrical shock, fire, or explosion which may result in injury, death or property damage.
 - Never Smoke or allow Spark of Flame in vicinity of Battery or Engine.
 - Never Jump-Start or Charge a frozen battery.
 - Jump-Start in well ventilated area only a spark can cause explosion.

MINORS. If the product is intended by "Purchaser" to be used by a minor, purchasing adult agrees to provide detailed instructions and warnings to any minor prior to use. Failure to do so is the sole responsibility of the "Purchaser", who agrees to indemnify Antigravity Batteries for any unintended use or misuse by a minor.

CHOKING HAZARD. Accessories may present a choking hazard to children. Do not leave children unattended with product or any accessory. The product is not a toy. Whether stored or in use, keep this product out of reach of children. Close supervision is necessary when used near children.

HANDLING. Handle product with care. The product can become damaged if impacted. Do not use a damaged product, including, but not limited to, cracks to the casing or damaged power cords/cables, swollen battery or case. Humidity and liquids may damage product. Do not handle product or any electrical components near any liquid. Store and operate product in dry locations. Do not operate products if it becomes wet. If product is already operating and becomes wet, disconnect it from the battery and discontinue use immediately. Do not disconnect the product by pulling on the cables.

MODIFICATIONS. Do not attempt to alter, modify or repair any part of the product. Disassembling product may cause injury, death or damage to property. If product becomes damaged, malfunctions or comes in contact with any liquid, discontinue use, and contact Antigravity Batteries. Any modifications to the product will void your warranty.

ACCESSORIES. This product is only approved for use with Antigravity Batteries accessories. Antigravity Batteries is not responsible for user safety or damage when using accessories not approved by Antigravity Batteries.

LOCATION. Prevent battery acid from coming in contact with the product. Do not operate the product in a closed-in area or an area with restricted ventilation. Do not set a battery on top of product. Position cable leads to avoid accidental damage by moving vehicles parts (including hoods and doors), moving engine parts (including fan blades, belts, and pulleys), or what could become a hazard that may cause injury or death.

OPERATING TEMPERATURE. This product is designed to work in ambient temperatures between -30 degrees C to 50 degrees C. Do not operate outside of temperature ranges. Do not jump start a frozen battery. Discontinue use of product immediately if the battery becomes excessively warm or bulges (appears swollen).

STORAGE. Do not use or store your product in areas with high concentrations of dust or airborne materials. Store your product on flat, secure surfaces so it's not prone to falling. Store your product in a dry location. The storage temperature is 0 degrees C to 43 degrees C (average temperature). Never exceed 80 degrees C under any condition.

COMPATIBILITY. The product is only compatible with 12-volt lead-acid batteries only. Do not attempt to use product with any other type of battery. Jump starting other battery chemistries may result in injury, death or property damage. Contact the battery manufacturer prior to attempting to jump start the battery. Do not jump start a battery if you are unsure of the battery's specific chemistry or voltage.

THE BATTERY. The built-in lithium-ion battery in the product should be replaced only by Antigravity Batteries, and must be recycled or disposed of separately from household waste. Do not attempt to replace the battery yourself and do not handle a damaged or leaking lithium-ion battery. Never dispose of battery in household trash. Disposal of batteries in household trash is unlawful under state and federal environmental laws and regulations. Always take used batteries to your local battery recycling center. If the product battery is excessively hot, emitting an odor, deformed, cut, or is experiencing or demonstrating an abnormal occurrence, immediately stop all use and contact Antigravity Batteries. This jump starter is not designed to be used as a replacement for a vehicle's battery.

BATTERY CHARGING. Charge the products only with the included/supplied AC or DC chargers. Failure to do so may result in electrical shock, fire, explosion which may result in injury, death or property damage. Some third-party USB C cables and 5W or 10W power adapters that are compatible with USB 2.0 or power adapters compliant with one or more of the following standards EN 301489-34, IEC 62684, YD/T 1591-2009, CNS 15285, ITUL1000 may be used on the XP-3 and XP-10 models.

Be cautious of using low quality USB power adapters, as they may present a serious electrical risk that can result in injury to person, device, and property. If using a third party USB power adapter, contact the manufacturer(s) to find out if your power adapter complies with the above standards.

Using damaged cables or chargers, or charging when moisture is present, can result in a electric shock. Using generic or third-party power adapter may shorten the life of your product and cause the product to malfunction. Antigravity Batteries is not responsible for the user's safety when using accessories or supplies that are not approved by Antigravity Batteries.

When using a USB Power Adapter to charge the product (XP-3 or XP-10), make sure that the USB plug is fully inserted into the adapter before you plug it into a power outlet. Power adapters may become warm during normal use, and prolonged skin contact may cause bodily injury. Always allow adequate ventilation around power adapters when using them.

To ensure maximum battery life, avoid charging your product for more than 2 days at a time, as overcharging may shorten battery life. Over time, an unused product will discharge and must be recharged before use. Disconnect the product from power sources when not in use. Use the product only for their intended purposes. Never leave a battery product unattended while charging.

MEDICAL DEVICES. Product may emit electromagnetic fields. Product contains magnetic components which interfere with pacemakers, defibrillator, or other medical devices. These electromagnetic fields may interfere with pacemakers or other medical devices. Consult with your physician prior to use if you have any medical device including pacemakers. If you suspect the product is interfering with a medical device, stop using the product immediately and consult your physician.

MEDICAL CONDITIONS. If you have any medical condition that you believe could be affected by product, including but not limited to: seizures, blackouts, eyestrain or headaches, consult your physician prior to use of product. The use of the integrated high-powered flashlight in Strobe mode may harm persons with a light sensitivity or photosensitive epilepsy, which may result in serious injury or death.

LIGHT. Staring directly into the light beam or shine of the flashlight may result in permanent eye injury. The product is equipped with a high output LED pre-focused lamp that emits a powerful beam at the highest setting.

CLEANING. Power off the product before attempting any maintenance or cleaning. Clean and dry product immediately if it comes in contact with liquid or any type of contaminant. Use a soft, lint-free (microfiber) cloth. Avoid getting moisture in openings.

EXPLOSIVE ATMOSPHERES. Obey all signs and instructions. Do not operate product in any area with a potentially explosive atmosphere, including fueling areas or areas which contain chemicals or particles such as grain, dust or metal powders.

HIGH-CONSEQUENCE/RISK ACTIVITIES. This product is not intended for use where the failure of the product could lead to injury, death or severe environmental damage.

RADIO FREQUENCY INTERFERENCE. Product is designed, tested, and manufactured to comply with regulations governing radio frequency emissions. Such emissions from this product can negatively affect the operation of other electronic equipment, causing them to malfunction.

USE COMMON SENSE. Always remain aware of your surroundings and the potential for dangerous situations when using this product or working with Batteries.

MICRO-START

XP-3

USERS MANUAL

USE PRODUCT ONLY AS INTENDED!

⚠ DANGER- WARNING

PRIOR TO USE, READ AND UNDERSTAND PRODUCT SAFETY INFORMATION GUIDE AND THIS USERS MANUAL.

Failure to follow the instructions may result in **ELECTRICAL SHOCK, EXPLOSION, or FIRE, which may result in SERIOUS INJURY, DEATH, DAMAGE TO DEVICE or PROPERTY.** Do not discard this information.

By ANTIGRAVITY BATTERIES

WELCOME

Thank you for purchasing the Antigravity Batteries MICRO-START XP-3. The XP-3 is an ultra-compact Jump-Starter and Personal Power Supply. Just charge it and take a Personal Power Supply with you wherever you go, no electricity needed. It can jump-start your vehicles, and charge your USB Devices like Phones, Tablets, Go-Pro Cameras, and more. It comes in a complete kit with Carry Case.

Please read and understand the User Guide and Product Safety Information before operating the product!

For more information feel free to Contact us.

Antigravity Batteries
15622 Broadway Center St.
Gardena CA,
90248

www.antigravitybatteries.com
www.themicrostart.com
info@antigravitybatteries.com
310 527 2330

GETTING STARTED

The MICRO-START XP-3 comes partially charged out of the box and should be fully charged prior to use. Carefully read and understand the vehicle owner's manual on specific precautions and recommended methods for jump starting your particular vehicle. Make sure to determine the voltage of your vehicle's system and type of battery by referring to your battery owner's manual prior to using this product. The XP-3 is for jump-starting 12-volt starter batteries only.

BEFORE CONNECTING TO ANY BATTERY

Before connecting to the vehicle's battery, verify that you have a 12-volt battery system. The XP-3 is not suitable to jump-start any other voltage of battery. Identify the correct polarity of the battery terminals on the battery. The positive battery terminal is normally RED and marked by these symbols or letters (POS, P, +). The negative battery terminal is typically BLACK and marked by these letters or symbols (NEG, N, -). Do not make any connections to the carburetor, fuel lines, or thin metal parts for grounding. These instructions are for a negative ground system (most common). If your vehicle is a positive ground system (very uncommon), follow the instructions in reverse order.

SAFETY + PRECAUTIONS

READ AND UNDERSTAND ALL SAFETY INFORMATION BEFORE USING THIS PRODUCT. FAILURE TO FOLLOW THESE SAFETY INSTRUCTIONS MAY RESULT IN ELECTRICAL SHOCK, EXPLOSION, FIRE, WHICH MAY RESULT IN SERIOUS INJURY, DEATH OR PROPERTY DAMAGE.

- Do not leave the product in, or expose product to extremely high temperatures such as on dashboards or other extremely hot areas above 110 °F - 43 °C.
- Do not use product for any use other than intended.
- Do not use Jump-Start Port to power devices, it is ONLY for Jump-Starting.
- Do not Jump-Start with less than 3 lights lit on Capacity Indicator.
- Do not Jump-Start more than 5 seconds per attempt (overheating may occur).
- Do not Jump-Start more than 3 attempts in a row without allowing to cool.
- Do not allow the XP-3 to become wet, do not immerse in water.
- Do not operate the appliance in explosive atmospheres, such as in the presence of flammable liquids, gases or dust.
- Do not modify or disassemble, there are no serviceable parts inside
- Do not use as a replacement battery for vehicles.
- Do not leave the XP-3 connected to vehicle. Remove within 40 seconds of starting vehicle.
- Do not clamp the Red and Black Clamps together.
- Do not allow Children to play with this product un-supervised. Not recommended for use by infirm persons.
- Do not leave battery products unattended while charging.
- Do not charge frozen batteries, charge only between 0 °C and 40 °C
- Do not store in locations where the temperature may exceed 50 °C

OPERATING PRECAUTIONS

- Make sure the BLUE PLUG for the SMART-CLAMPS is plugged-in and seated fully into the XP-3. This connection must be good or it could over-heat the unit.
- Make sure to check all the battery connections are clean. Remove corrosion or dirt that prevents a solid connection of clamps to vehicle battery terminals.
- Make sure clamps have a good "bite" on Battery Terminals for the most power.
- Make sure the XP-3 has a minimum 3 lights on the Capacity Indicator lit before Jump-Starting.
- Make sure to remove the product from the vehicle battery within 40 seconds of Jump-Starting.
- Remove Clamps from XP-3 when not in use.

+ PRODUCT OVERVIEW

+ INCLUDED KIT ITEMS

+ PRODUCT SPECS

MODEL: MICRO-START XP-3

| | |
|--------------------------------|---------------------------------|
| CAPACITY: 8,000mah / 29.6WH | OUTPUT VOLTAGE: 11.8v |
| DIMENSION: 6" x 3" x 1.0" | 2 USB OUTPUTS: 5V - 2A, 5V - 1A |
| CHARGE MODE: CC/CV 14V - 1A | START CURRENT: 200A |
| CYCLE LIFE: 1,000 | PEAK CURRENT: 400A |
| OPERATING TEMP : -30°C to 50°C | CHARGING TEMP : 5°C to 40°C |

+ PRODUCT USE

CHECKING THE AVAILABLE CAPACITY

- 1) To check the state of charge/capacity on the XP-3 press the Power Switch. The XP-3 has a lighted capacity indicator which will show the state of charge.
- 2) Each light lit is equal to 25% capacity.

1 light=25% 2 lights=50% 3 lights=75% 4 lights=100%

***The XP-3 can charge electronic devices until no more lights are lit, but should only be used to jump-start with a minimum of 3 lights lit.**

LED FLASHLIGHT OPERATION

- 1) Press and hold the Power Switch for 3-4 seconds to turn-on the LED Flashlight
- 2) The Flashlight has 3 light patterns (Normal Flashlight, SOS and Strobe).
- 3) You can cycle to the next LED pattern by pressing the Power Switch again.
- 4) After the last Flashlight pattern, the unit will turn off the Flashlight.

***DO NOT STARE INTO THE LED FLASHLIGHT, PERSONAL INJURY MAY RESULT**

CHARGING THE XP-3

NEVER USE ANY OTHER CHARGERS THAN THOSE PROVIDED. FIRE, EXPLOSION, PERSONAL AND PROPERTY DAMAGE MAY OCCUR.

The XP-3 comes with 2 chargers for charging at Home or in your Vehicle: a Wall Plug AC Charger, and a DC Cigarette Lighter Charger. It may also be charged by any USB Outlet, just plug a USB Cable into its MICRO-USB Port.

When charging, the indicator lights will flash one by one. The number of solid lights lit indicates the XP-3 charge level. All lights solidly lit indicates a fully charged XP-3. After a full charge the unit will turn off the capacity lights.

- 1) To charge, plug the provided chargers or a Micro-USB Cable into the XP-3 to begin charging.
- 2) When fully charged remove charger. Do not leave charging over 24 Hours.

***NEVER LEAVE ANY DEVICES UNATTENDED DURING CHARGING.**

CHARGING USB DEVICES

The XP-3 can charge any USB 5v devices at 2.1 or 1.1 Amps, such as Smart Phones, Tablets, GPS Devices, GoPro Cameras and more.

- 1) Plug the provided 4-into-1 USB Cable or any standard USB Cable into either USB Output Port on the XP-3, plug the other end of the cable into the device you are charging.
- 2) Press the Power Switch on the XP-3 to begin charging your device.
- 3) Disconnect your Device when charged.

*Note: The number of times devices can be charged will vary depending on the size of your device's battery.

JUMP STARTING A VEHICLE

The XP-3 is equipped with SMART CLAMPS that have built-in protections to prevent accidental reverse-polarity connections, over-charge and more. But caution should always be used when Jump Starting. READ ALL INSTRUCTIONS AND SAFETY GUIDE FULLY BEFORE USING THIS PRODUCT.

- 1) Make sure all the Vehicle's Lights, Radios, Air Conditioning and Accessories are turned off. Confirm you are connecting to a 12-Volt Battery System only.
- 2) Connect the Smart-Clamps to the Battery of the Vehicle. Red Clamp to Positive (+) Terminal of Battery. Black Clamp to Negative (-) Terminal of Battery. Remove any corrosion from the Vehicle Battery Terminals to make a good connection.
- 3) Connect the XP-3 to the Smart-Clamps.
- 4) One of the following LED LIGHT indications will show on the Smart-Clamps.
 - a) **GREEN LED** - Indicates the XP-3 is connected correctly and you can proceed to start the vehicle. **Go to Step 5.**
 - b) **GREEN LED FLASHING** - This indicates your Vehicle Battery has very low voltage, but the connection is CORRECT. In this case you will need to press the "BOOST" Button on the Smart Clamps and attempt to start. **Go to Step 5.**
 - c) **RED LED** - Indicates your connection to the vehicle battery is INCORRECT. Remove the Clamps, correct the connections and **Go to STEP 1.**
 - d) **NO LED LIGHTS** - This indicates there is no vehicle battery or the vehicle's battery is below 2-volts. In this case you will need to make sure you have the clamps properly connected per **Step 2**, THEN press the "BOOST" Button. **Go to Step 5.**
- 5) Attempt to Start the Vehicle. After starting your vehicle, leave it running, but disconnect the MICRO-START AND SMART-CLAMPS within 40 seconds of starting. DO NOT LEAVE ATTACHED.

USING THE BOOST BUTTON

EXTREME CAUTION MUST BE USED WHEN PRESSING THE BOOST BUTTON ON THE SMART-CLAMPS. THE BOOST BUTTON MAKES THE CLAMPS "LIVE" WITH CURRENT AND BY-PASSES THE BUILT-IN SAFETY FEATURES.

HIGH AMPERAGE, AND POTENTIAL FOR HEAT, SPARKS AND PROPERTY DAMAGE MAY OCCUR IF THE SMART-CLAMPS ARE NOT CONNECTED CORRECTLY. ONLY USE THE BOOST BUTTON WHEN CLAMPS HAVE BEEN CORRECTLY CONNECTED TO THE PROPER POLARITY ON THE VEHICLE'S BATTERY. IF YOU ARE UNSURE WITH USE CONTACT US AT: 310 527 2330 OR: INFO@ANTIGRAVITYBATTERIES.COM

USING THE "BOOST" BUTTON ON THE SMART-CLAMPS.

In most circumstances you will not need to use the Boost Button on the Smart Clamps. The "Boost" Button is intended to allow for Jump Starting a Vehicle when the battery has very low voltage, or no voltage reading. In these circumstances the "Boost" Button allows the clamps to be energized to start the Vehicle for emergency Jump-Starting.

CAUTION MUST BE USED WHEN PRESSING THE BOOST BUTTON! THE CLAMPS ARE LIVE WITH ENERGY ONCE PUSHED. PLEASE NOTE THE FOLLOWING.

- A) The Smart-Clamps must be connected to the XP-3 for the "Boost" Button to operate.
- B) BEFORE pressing the "Boost" Button make sure all connections are correct. Once the "Boost" Button is pressed the Clamps will have "live" voltage at the Clamps. Always connect Red Clamp to Positive (+) Terminal of Battery. Black Clamp to Negative (-) Terminal of Battery.
- C) The "Boost" Button will "click" when pressed correctly, you may need a pen, finger nail or edge of the key to press the button correctly due to the "Boost" Button being indented in the Smart-Clamp Housing.
- D) Once the "Boost" Button is pressed you have 25 seconds to attempt your jump-start, after that time the "Boost" will turn-off. You will need to press the Boost Button again to re-engage the Boost feature.

WARNINGS

-DO NOT USE THE JUMP START PORT FOR ANYTHING BUT JUMP STARTING! -DO NOT LEAVE THE MICRO-START UNIT CONNECTED TO THE VEHICLE! -DO NOT PRESS THE "BOOST" BUTTON ON CLAMPS IF CLAMPS ARE CONNECTED TOGETHER! THE BOOST BUTTON IS A BYPASS AND MAKES THE CLAMPS LIVE WITH ENERGY! USE CAUTION.

FREQUENTLY ASKED QUESTIONS

Q. How do I turn off the XP-3?
The XP-3 will automatically power-off when it is not powering anything. Usually in about 15 seconds. Disconnect the Clamps when not in use.

Q. How many times can the XP-3 charge a Cell Phone?
The XP-3 can charge the average Phone about 4-7 times depending on the size of the cell phone's battery. It has 8,000mah of capacity.

Q. How many times can it charge a Tablet?
The Microstart XP-3 can generally charge a Tablet from 2-3 times. This depends on the size of the Tablet's battery.

Q. How long does it take to fully charge?
The XP-3 can fully charge from completely dead in 4 hours. If there is some charge in the XP-3 it can charge in much less time.

Q. How long will it take to charge my cell phone?
The XP-3 can charge a phone in about 40-60 minutes. It depends on the phone's battery size, but the XP-3 does charge USB Devices fast because it has a 2-amp charge rate on one of the USB ports.

Q. How many times can it start a car?
This depends on the size of the motor and state of charge, but modern V8s about 15 times on one charge. It is not intended to start Diesel Motors!

Q. How long can the XP-3 hold a charge?
On average the XP-3 can hold a charge for up to 6-7 months. This will depend on the conditions it is stored in. Heat and cold can affect this. It is best to check the state of charge at least once every 3-4 months.

Q. Can I use the Jumper Clamps or Starter Port to power other things?
No, this should not be done. The Jumper Clamp port and clamps should only be used to jump-start vehicles with a minimum of 3 lights lit for the following conditions: Other uses, such as powering other electronics through this port, will ruin the device and could cause personal property damage, explosion or fire.

Q. How big of a motor can the XP-3 start?
This depends on the vehicle and how good of a connection you have to the vehicle. Modern V8 Motor up to 5 Liters can be done fairly easily. Diesels are a much harder start than Gas Motors. The XP-3 is not intended to start Diesel Motors. Use the MICRO-START XP-10 for that use.

LIMITED WARRANTY NON-TRANSFERABLE

ANTIGRAVITY Batteries LLC (ANTIGRAVITY) warrants that its products (the "Product") will be free from defects in material and workmanship for a period of one (1) year from the date of purchase (the "Warranty Period"). For defects reported during the Warranty Period, ANTIGRAVITY will, at its discretion, and subject to ANTIGRAVITY's technical support analysis, either repair or replace, for the fees set forth below. Replacement parts and products will be new or serviceably used, comparable in function and performance to the original part and warranted for the remainder of the original Warranty Period.

THE FOREGOING LIMITED WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES NOT EXPRESSLY SET FORTH HEREIN, WHETHER EXPRESSOR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ANTIGRAVITY'S LIABILITY UNDER THIS LIMITED WARRANTY IS EXPRESSLY LIMITED TO REPLACEMENT (IN THE FORM AND UNDER THE TERMS ORIGINALLY SHIPPED), OR TO REPAIR, WHETHER SUCH CLAIMS ARE FOR BREACH OF WARRANTY OR FOR NEGLIGENCE. ANTIGRAVITY SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL, OR SPECIAL LOSSES, DAMAGES OR EXPENSES OF ANY KIND, INCLUDING, WITHOUT LIMITATION, ANY SUCH LOSSES, DAMAGES, OR EXPENSES ARISING DIRECTLY OR INDIRECTLY FROM THE SALE, HANDLING, OR USE OF THE PRODUCT FROM ANY OTHER CAUSE RELATING THERETO, OR FROM PERSONAL INJURY OR LOSS OF PROFIT.

Some states, provinces and countries do NOT allow the exclusion or limitation of incidental or consequential damages or length of an implied warranty so the above limitation(s) or exclusion(s) may NOT apply. This Limited Warranty gives you specific legal rights and you may also have other legal rights, which vary by state, province and country.

Limited Warranty.
This Limited Warranty is made to the original purchaser from ANTIGRAVITY and does NOT extend to any other person or entity and is NOT assignable. It is the obligation of the original purchaser to:
1) Request and obtain a return merchandise authorization (RMA) number from ANTIGRAVITY Support at info@antigravitybatteries.com.
2) Forward the Product, including RMA number, payment for any applicable fees, and Proof of Purchase prepaid to: Antigravity Batteries, Attn: Warranty Department, 15622 Broadway Center St., GARDENA, CA 90248

THE COSTS OF TRANSPORTING PRODUCTS TO ANTIGRAVITY FOR WARRANTY SERVICE IS THE RESPONSIBILITY OF THE ORIGINAL PURCHASER. THIS LIMITED WARRANTY IS VOID UNDER THE FOLLOWING CONDITIONS:
1) The Product is misused, subjected to careless handling, or operated under conditions of extreme temperature, shock, or vibration beyond ANTIGRAVITY's recommendations for safe and effective use.
2) The Product has NOT been installed, operated, or maintained in accordance with approved procedures.
3) The Product is disassembled, altered, or repaired by anyone, except ANTIGRAVITY.
4) The electrical connections to the DC output, input ports, jump-start port, USB port of the product are modified without the express written consent of ANTIGRAVITY.
5) The Product is subject to improper storage or accident.
6) The original purchaser fails to register the product.
7) The product is charged by any other charger than supplied or approved by ANTIGRAVITY.
8) The Product has been used outside its intended use.

LIMITED WARRANTY CONTINUED

THIS LIMITED WARRANTY DOES NOT COVER:
1) Normal wear and tear.
2) Cosmetic damage that does NOT affect functionality.
3) Products where the ANTIGRAVITY Serial number is missing, altered, or defaced.

LIMITED WARRANTY FEES
These fees apply only to Product during the Warranty Period. The Limited Warranty is void either by elapsed time from date of purchase or from the conditions listed earlier in this document. Return Product with the appropriate documentation along with a check for the applicable fees, as set forth below. Make checks payable to THE ANTIGRAVITY Company. With Receipt: 0 Years. No Charge. NO Receipt: 0-1 Years: 45% of MSRP (Exact amount will be verified when RMA is issued)

REGISTER YOUR ANTIGRAVITY PRODUCT
You MUST register your ANTIGRAVITY product in order to validate the Limited Warranty. You can register the product Online. To register your product Online, please visit: themicrostart.com/warranty/registration. Complete the requested information and click "send".

NOTES:

ANTIGRAVITY BATTERIES

VISIT OUR WEBSITES FOR MORE COOL PRODUCTS, ACCESSORIES AND INFO

antigravitybatteries.com
shop.antigravitybatteries.com
themicrostart.com

CONTACT INFORMATION

Email: info@antigravitybatteries.com
Phone: 310 527 2330

PLEASE READ THE "PRODUCT SAFETY INFORMATION GUIDE" BEFORE USING PRODUCT.

